

Setting up PageStore 3.1 in Mac OS X



How to install, authenticate and configure PageStore 3.1 on a Macintosh

Installation

- Select an installation scenario and download the required installation package:

Single-user	PageStore3_AllInOne.dmg
Multi-user	PageStore3_MultiUser.dmg
- Install the single-user package on Mac OS X , OR
- For a multi-user package:
 - Install the **PageStore DB Server** on a Mac OS X Server.
 - Copy the **Quickcut** folder on the same or another networked Mac server.
 - Install the **PageStoreNetworkClient** on Mac OS X.

Note: The Macintosh server can only support Mac clients. The Windows server can support both.

Authentication

You need to authenticate PageStore 3 the first time you run it on each client machine.

- Open the PageStore 3 application.
You will see an Authentication message.
- For a demo version or pre-release, type **demo** in the **Serial #** field, then enter the Authentication code provided by Adstream.
- For a full version, fill in all the fields and click **Fetch Authentication #**. When the code is displayed, copy it into the **Authentication** field.
- Click the **Authenticate** button.

Connecting a client to the server

For a single-user installation, simply start PageStore.

For a multi-user installation, proceed as follows:

- Make sure the appropriate PageStore 3 server is running and the client Mac has network access to it.

- Open and authenticate the PageStore 3 application on the first client machine.
- The Configure PageStore Server IP dialog appears.
- To connect to the server you want, EITHER type in its IP address OR click its name on the list at the bottom of the window. (On a PC, the list will only appear if Bonjour is installed on the client and the servers.)
- If using an IP address, click **Check** to ensure that the selected server is available.
- A message appears: **Successfully connected to service.**
- Click **Continue**.

Logging in

- When the login window appears, log in as **Username: setup, Password: setup**.
- When the Licence Agreement appears, click on **Agree**.

Configuring the site code

- A message will appear if your Site Code is not configured.
- Click **OK** and proceed as follows:
 - Log out, then log in as PageStore Support. Technical Support will supply instructions and a password which can be used once only.
 - Open the **PageStore** menu and select **Preferences**.
 - Click the **Comms** icon.
 - Enter your 4-character client user name and your client user password.
 - Click **Confirm**.
 - Click the **Admin** icon.
 - Enter the 4-character client user name and other client information.
 - Close the Preferences window.
 - Log out, then log in as a user.



Locating the database and workspace files

- Mount the server which contains the database and workspace files.
- If the server requires log-in access, log in.
- In the PageStore client, select **Preferences** from the **PageStore** menu.
- Click the **Paths** icon.
The paths which need to be set are shown in **red**.
- Click the **Browse** button to locate the **Database** folder.
- Once the Database folder has been identified, PageStore 3 may automatically set the remaining paths. If not, use the **Browse** button to locate the correct **Outgoing**, **Sent** and **Working** folders.

Once the paths have been set for the first client, all other clients which connect to the same server will have the correct paths. Start each of the remaining clients and connect to the server as described above.

Creating user accounts

- While logged in as the **setup** user, create login accounts for all the client users:
 - Open the **PageStore** menu and select **Preferences**.
 - Click the **Login** icon.
 - Click **New** and enter suitable user details.
 - Click **Update** after entering each new user.
 - Click **OK** to finish.

For more details, contact Technical Support on 1300 768 988 or email support@quickcut.com.au. For up-to-date information on PageStore 3, go to <http://www.quickcut.com.au/support/qc/ps/pagestore.html>.
